



## OVERVIEW

Our most compact Hog yet! The Hoglet 4 is a compact programming wing, designed for tight spaces and small productions such as clubs, churches and small concert venues. Combine the Hoglet 4 with Hog 4 PC and you are ready to rock!

Even a seasoned Hog programmer will feel right at home on the Hoglet 4, as it has a programming surface similar to its larger brothers. Combine Hoglet 4, Hog 4 PC and a touchscreen and you have a proper, full-fledged lighting console with four DMX ports and four encoders built in.

Hoglet 4 is also a great companion to the Rack Hog 4, as it makes operating a show in a confined space or programming fixed-installations a breeze.

### PRODUCT FEATURES

- USB connection to Rack Hog 4, Hog 4 PC, or any Hog 4 family console
- Full programming keypad
- Four expanded-wheelset encoders
- 12 user-assignable function keys
- 10 non-motorized playback masters with go, halt, choose and flash keys
- Master column and paging button
- 4 Neutrik XLR-5 DMX outputs

## ORDERING INFORMATION

### Hoglet 4 Programming Wing

MODEL	DESCRIPTION
61040064	Hoglet 4 programming wing

Ships with: one dimmable white desk light, dust cover, external PSU.

### Additional Accessories

MODEL	DESCRIPTION
61080011	Hoglet 4 programming wing dust cover, replacement
A2080004	Hog white desk light, replacement
61070016	Hoglet 4 programming wing road case
74040011	USB DMX Widget
74040008	USB DMX Super Widget
62040005	USB DMX Super Duper Widget
74040009	USB MIDI/LTC Widget

## PRODUCT SPECIFICATIONS

### SPECIFICATION

- USB connection to Rack Hog 4, Hog 4 PC, or any Hog 4 family console
- Full programming keypad
- Four expanded-wheelset encoders
- 12 user-assignable function keys
- 10 non-motorized playback masters with go, halt, choose and flash keys
- Master column and paging button
- 4 Neutrik XLR-5 DMX outputs

### INTERFACES AND ACCESSORIES

- Built-in DMX Super Widget
- Local DMX-512 outputs: 4x Neutrik 5-pin XLR
- Expandable DMX-512 outputs via USB DMX Widgets
- USB 2.0 ports: 2 rear

### ELECTRICAL AND ENVIRONMENTAL

- ETL, CETL and CE compliance
- External PSU input: 100-250VAC, 50/60Hz, max 25W
- External PSU output: 12VDC 2.5A/25W

### HOGLET 4 DIMENSIONS

MODEL	HEIGHT		WIDTH		DEPTH		WEIGHT	
	in	mm	in	mm	in	mm	lb	kg
Hoglet 4 programming wing	2.6	67	23.8	603	12.4	314	8.7	3.9