



Road Hog USB to VGA Adapter Kit

Quick Start Guide

The Road Hog USB to VGA Adapter Kit allows you to connect an additional monitor or touchscreen to your Road Hog console via a USB port.

The USB to VGA adapter used to control the extra screen uses very little computer resources and offers a vast array of screen resolutions and color depths. This ensures that there is little difference in performance between a directly connected screen and a screen connected through the USB VGA Adapter.

The USB to VGA Adapter supports all analogue CRT and LCD monitors with a VGA connector. DVI- A and DVI- I monitors can also be connected using a suitable VGA DVI converter. Only one USB to VGA Adapter can be connected to the Road Hog console at a time. If you attach more than one module to a Road Hog console, only one will be active.

The kit includes:

- One Iogear USB 2.0 External Video Card (USB to VGA Adapter)
- One USB 2.0 Cable
- One Quick Start Guide

Power

The USB to VGA Adapter is able to run from power supplied by the Road Hog's USB bus and should operate without any problems on the majority of configurations. However if problems do occur, a 5V 400mA supply should be used for external power to the USB to VGA Adapter.

VGA Support

The VGA output on the USB to VGA Adapter is via a standard 15- pin HD Sub- D connector. This should be connected directly to a computer monitor. The VGA connector may be plugged and unplugged while the USB VGA Adapter is on. Below is a list of refresh rates supported at various resolutions and color depths for the USB to VGA Adapter:

	Color Depth	640x480	800x600	1024x768	1280x960	1280x1024
Refresh	16 bit	60 72 75	56 60 72 75 85	60 70 75 85	60 85	60 75 85
Refresh	24 bit	60 72 75	56 60 72 75 85	60 70 75 85	60 85	60 75

Installing the Adapter

Note: Road Hog XPe Image v1.1.2 or greater is required for support of the USB to VGA Adapter.

1. Connect the adapter to a USB port on the Road Hog console.
2. Connect a monitor to the VGA port on the USB to VGA adapter.
3. Turn on the Road Hog console.
4. Configure the external monitor in the *Displays* pane of the *Control Panel*: Setup -> Control Panel -> Displays.
5. Refer to section 12.1.3 of the Wholehog User Manual or Help for further details.

If you experience any complications or have any questions regarding these installations, contact the High End Systems Service Hotline at 1.800.890.8989 to speak with a technician.

HIGH END SYSTEMS®



P/N 60600290