



Road Hog 4 Lighting Control Console

- Operating System: Hog 4 OS (Linux Kernel)
- Built in DMX Processor 8000
- Oversized Built-In Touchscreen
- Built-in Kensington Security Lock
- Desk light included
- Light Converse Visualizer dongle included
- Dust cover included
- Custom Road Case Available

CONTROL SURFACE:

Playback Faders: 10, manual
GrandMaster: shared with playback fader 1
Encoder Wheels: 4 with dedicated function buttons
Function Keys: 12
KeyBoard: Support for external USB keyboard
Trackball: external USB trackball support
Desklight: 1, dimmable blue and white LEDs
Worklight: Yes, dimmable white LED
Ventlight: Yes, dimmable blue LED

ELECTRICAL

Voltage: 100-240VAC ,50 / 60Hz
Max Current: 5A
Mains Connector: IEC 320

PHYSICAL

Weight: 38.6 lbs (17.5 kg)
Dimensions: 26.7" (678.18mm) wide
27.61" (701.32mm) deep
8.10" (205.8mm) high

DISPLAYS

Internal: One 22" widescreen touchscreen
(10 point multi-touch)
External: Support for one monitor / touchscreen
(DVI-D or VGA - only one can be used at a time)
(see Hog4OS manual for list of supported touchscreens)

DMX / ARTNET / SCAN

Local Output Processing: 8 universes (4,096 ch)
Local DMX Outputs: 4 x Neutrik 5-pin female XLR
Expansion via external DP8000s: Yes, Unlimited

I/O CONNECTIVITY

USB 2.0 Ports: 2 rear, 1 front
USB 3.0 Ports: 2 rear
HogNet: Yes (allows connectivity to other consoles)
MIDI: Support for external USB Midi class devices
(supports MIDI Show Control, MIDI Timecode , and MIDI Notes)
LTC Input: Requires separate USB LTC Widget
FixtureNet: Yes (Art-Net, sACN, Visualizer connect)
Visualizer connectivity: FixtureNet / Art-Net / sACN
(list of supported visualizers in Hog 4 OS help manual)
Remote Focus: Yes, via Open Sound Control

COMPUTER

Motherboard: Advantech AIMB-581
CPU: Intel Pentium G850 2.9 Ghz
Memory: 4 GB
Internal Hard Drive: 32 GB SSD
Internal CD-R/DVD-ROM: No