

	Technical Bulletin	High End Systems	Page 1/1
	Replacing the Full Boar 4 Bios Battery	21-Dec-2012	Rev A

This document describes how to change the BIOS battery in a Full Boar 4 Console. High End Systems recommends using a new Panasonic CR2032 when replacing an old battery.

A video demonstration of this procedure can be found here:

<http://www.highend.com/hesdirect/hog4/Fb4biosreplacement.asp>



Warning: Unplug console power before beginning this procedure.

CHANGING THE BATTERY

1. Disconnect the console desk lights. Remove the six screws located around the touch screens on the front of the console using a 3mm hex tool.
2. Remove the three remaining screws from the back of the console using a 2.5mm hex tool.
3. Remove the grey top metal housing from the console.
4. From the back of the console tilt the top of touchscreen assembly forward towards the front of the console so that you have access to the motherboard.
5. Push the bios battery retaining clip to the side and remove the bios battery.
6. Insert a new bios battery and reassemble console by performing steps 4 thru 1 in reverse.
7. Plug a USB keyboard into your console. Power on the console while holding the delete key on the USB keyboard.
8. When the BIOS menu appears use the keyboard to navigate to the date and time settings and set the correct date and time. Then navigate to the exit and save menu and select the "Restore Defaults" option. Then select "Save Changes and Exit". The console will reboot.